


IGBT Discrete

V_{CE}	1200	V
I_C	140	A
$V_{CE(SAT)} I_C=140A$	1.75	V

Circuit



Applications

- Energy storage inverter
- Uninterruptible power supplies
- Solar inverters

Features

- High breakdown voltage to 1200V for improved reliability
- Maximum junction temperature 175°C
- Positive temperature coefficient
- Including fast & soft recovery anti-parallel FWD

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Breakdown Voltage	V_{CE}	1200	V
DC Collector Current, limited by T_{jmax} $T_C=25^\circ C$ $T_C=100^\circ C$	I_C	180 140	A
Diode Forward Current, limited by T_{jmax} $T_C=25^\circ C$ $T_C=100^\circ C$	I_F	180 140	A
Continuous Gate-Emitter Voltage	V_{GE}	± 20	V
Transient Gate-Emitter Voltage ($t_p \leq 10\mu s, D < 0.010$)	V_{GE}	± 30	V
Turn off Safe Operating Area $V_{CE} \leq 1200V$, $T_j \leq 150^\circ C$		280	A
Pulsed Collector Current, $V_{GE}=15V$, t_p limited by T_{jmax}	I_{CM}	280	A
Diode Pulsed Current, t_p limited by T_{jmax}	I_{Fpuls}	280	A
Power Dissipation, $T_j=175^\circ C$, $T_C=25^\circ C$	P_{tot}	937	W



Operating Junction Temperature	T_j	-40...+175	°C
Storage Temperature	T_s	-55...+150	°C
Soldering Temperature, wave soldering 1.6mm (0.063in.) from case for 10s		260	°C

Electrical Characteristics of the IGBT ($T_j = 25^\circ\text{C}$ unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Collector-Emitter Breakdown Voltage	BV_{CES}	$V_{GE}=0V, I_C=250\mu A$	1200		-	V
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=1mA$	5.4	5.9	6.4	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=140A$ $T_j=25^\circ\text{C}$, $T_j=125^\circ\text{C}$ $T_j=150^\circ\text{C}$		1.75 2.20 2.30	2.05	V
Zero Gate Voltage Collector Current	I_{CES}	$V_{CE}=1200V, V_{GE}=0V$ $T_j=25^\circ\text{C}$, $T_j=150^\circ\text{C}$			0.25 5	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{CE}=0V, V_{GE}=\pm 20V$			100	nA

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic						
Input Capacitance	C_{ies}	$V_{CE}=25V, V_{GE}=0V,$ $f=1\text{MHz}$	-	11.8	-	nF
Reverse Transfer Capacitance	C_{res}		-	0.13	-	
Gate Charge	Q_G	$V_{CC}=600V, I_C=140A,$ $V_{GE}=15V$	-	0.75	-	uC

**Electrical Characteristics of the Diode** (T_j= 25°C unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Diode Forward Voltage	V _F	I _F = 140A T _j = 25°C, T _j = 125°C T _j = 150°C		2.10 2.25 2.30	2.50	V

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T_j= 25°C						
Turn-on Delay Time	t _{d(on)}	V _{CC} = 600V, I _C =140A, V _{GE} = -5V~15V, R _g =5.1Ω	-	66	-	ns
Rise Time	t _r		-	132	-	ns
Turn-on Energy	E _{on}		-	13.3	-	mJ
Turn-off Delay Time	t _{d(off)}		-	167	-	ns
Fall Time	t _f		-	58	-	ns
Turn-off Energy	E _{off}		-	4.9	-	mJ
Dynamic , at T_j= 125°C						
Turn-on Delay Time	t _{d(on)}	V _{CC} = 600V, I _C =140A, V _{GE} = -5V~15V, R _g =5.1Ω	-	64	-	ns
Rise Time	t _r		-	124	-	ns
Turn-on Energy	E _{on}		-	13.5	-	mJ
Turn-off Delay Time	t _{d(off)}		-	173	-	ns
Fall Time	t _f		-	83	-	ns
Turn-off Energy	E _{off}		-	5.7	-	mJ
Dynamic , at T_j= 150°C						
Turn-on Delay Time	t _{d(on)}	V _{CC} = 600V, I _C =140A, V _{GE} = -5V~15V, R _g =5.1Ω	-	63	-	ns
Rise Time	t _r		-	120	-	ns
Turn-on Energy	E _{on}		-	13.6	-	mJ
Turn-off Delay Time	t _{d(off)}		-	180	-	ns
Fall Time	t _f		-	96	-	ns
Turn-off Energy	E _{off}		-	6.1	-	mJ











Electrical Characteristics of the DIODE





Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T_j= 25°C						
Reverse Recovery Current	I _{rr}	I _F =140A, V _R =600V, -di/dt= 850A/μs	-	48	-	A
Diode reverse recovery time	trr		-	288	-	ns
Reverse Recovery Charge	Q _{rr}		-	5.9	-	uC
Reverse Recovery Energy	E _{rec}		-	2.3	-	mJ
Dynamic , at T_j= 125°C						
Reverse Recovery Current	I _{rr}	I _F =140A, V _R =600V, -di/dt= 850A/μs	-	61	-	A
Diode reverse recovery time	trr		-	371	-	ns
Reverse Recovery Charge	Q _{rr}		-	10.7	-	uC
Reverse Recovery Energy	E _{rec}		-	4.4	-	mJ
Dynamic , at T_j= 150°C						
Reverse Recovery Current	I _{rr}	I _F =140A, V _R =600V, -di/dt= 850A/μs	-	67	-	A
Diode reverse recovery time	trr		-	413	-	ns
Reverse Recovery Charge	Q _{rr}		-	13.1	-	uC
Reverse Recovery Energy	E _{rec}		-	5.5	-	mJ





Thermal Resistance




Parameter	Symbol	Max. Value	Unit
IGBT Thermal Resistance, Junction - Case	R _{th(j-c)}	0.16	K/W
Diode Thermal Resistance, Junction - Case	R _{th(j-c)}	0.26	K/W
Thermal Resistance, Junction - Ambient	R _{th(j-a)}	40	K/W













Circuit Diagram



● Package Outline Information

CASE: TO 247plus



DIM	MILLIMETERS	
	MIN	MAX
A	4.90	5.10
A1	2.31	2.51
A2	1.90	2.10
b	1.16	1.26
b1	1.86	2.16
b2	1.96	2.06
c	0.58	0.64
D	20.90	21.10
D1	16.25	16.85
D2	1.05	1.35
D3	0.58	0.78
E	15.70	15.90
E1	13.10	13.50
E3	1.35	1.55
e	5.44(BSC)	
L	19.78	20.08
L1	4.03	4.23
R	1.90	2.10



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.