


Small Signal Schottky Diode



Features

- Moisture sensitivity level 1
- Reverse voltage: 40V/30V/20V
- Average forward current : 350mA

Application

- High frequency and low voltage rectifier

Mechanical data

- **Package:** SOD-123
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Value	
			SD103AW	SD103CW
Device marking code			S4	S6
			S5	
Repetitive peak reverse voltage	V _{RRM}	V	40	20
			30	
Forward current	I _F	A	0.35	
Non-repetitive surge peak forward current @ t=8.3ms half-sine wave	I _{FSM}	A	1.5	
Non-repetitive surge peak forward current @ t=1ms square wave			5	



SD103AW THRU SD103CW

RoHS
COMPLIANT

Parameter	Symbol	Unit	Value
Power dissipation	P_D	mW	400
Junction temperature	T_J	°C	-55 to +125
Storage temperature	T_{STG}	°C	-55 to +150

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Typ	Max	
Breakdown voltage	V_R	V	SD103AW	$I_R=100\mu A$	40		
			SD103BW		30		
			SD103CW		20		
Forward voltage	V_F	V	$I_F=20mA$			0.37	
			$I_F=200mA$			0.60	
Reverse leakage current	I_R	μA	SD103AW	$V_R=30V$			5.0
			SD103BW	$V_R=20V$			5.0
			SD103CW	$V_R=10V$			5.0
Junction capacitance	C_j	pF	$V_R=0V, f=1MHz$			50	

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	$R_{\theta J-A}^{(1)}$	°C/W	315
Thermal resistance, junction-to-case	$R_{\theta J-C}^{(1)}$	°C/W	252

Note:

(1) Thermal resistance from junction to ambient and from junction to case mounted on P.C.B. with 8mm*9mm copper pad areas



■ Characteristics

Fig 1: PD-TA Curve




Fig 2: Capacitance Capability




Fig 3: Typical Forward Characteristics





Fig 4: Typical Reverse Characteristic






SD103AW THRU SD103CW

RoHS
COMPLIANT

Ordering Information


Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
SD103AW THRU SD103CW	F2	Approximate 0.011	3000	30000	120000	7" reel
SD103AW THRU SD103CW	F3	Approximate 0.011	10000	/	210000	13" reel

Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.140	0.152	3.550	3.850
B	0.100	0.112	2.550	2.850
C	0.055	0.071	1.400	1.800
D	0.037	0.053	0.950	1.350
E	0.020	0.028	0.510	0.710
G	0.006	0.018	0.150	0.450
H	0.003	0.010	0.080	0.250
J	0.000	0.006	0.000	0.150
θ	0	8°	0	8°

Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.